



HIPER V
VERSATILE FUNCTION
GNSS RECEIVER



All-Purpose GNSS Receiver



- Vanguard Technology™
- Universal Tracking Technology
- Rugged, magnesium alloy construction
- Integrated form delivering full RTK, Static, Network functionality
- Fence Antenna™ evolution for optimal signal isolation and tracking

Compact, cable-free solution with Vanguard Technology for all GNSS positioning applications

Topcon raises the standard once again by adding Vanguard Technology with 226 channels, Universal Tracking Technology, and the Fence Antenna into the versatile and configurable HiPer V receiver. Universal Tracking Technology is an advanced firmware process that allows each of the 226 channels to be assigned to any satellite signal – providing an all-in-view satellite monitoring ability like never before.

Internal radio configurations


The HiPer V integrated receiver can be configured with the radio and cellular modem that best fits your needs. You can choose from either a far-reaching Digital UHF option or a secure and steady Spread Spectrum radio. Further, you can choose from HSPA, CDMA, or no cellular module. If you start your HiPer V investment with static only receivers, they can later be upgraded to include radio and cellular modules at one of many Topcon service facilities around the globe.

Rugged and waterproof

The HiPer V is designed rugged enough to perform on a real jobsite. It is also waterproof IP67, which means it can be submersed into water. The ports, speaker and battery door are all completely sealed from dust and water.

Voice alerts

Voice status messages keep you informed without having to look at the screen of the field controller, or the status lights above your head. Stay safe in traffic situations by looking at oncoming traffic rather than looking for the word “Fixed”.




Fence Antenna™ technology

This superior GNSS antenna element is light-weight, rugged, and sensitive enough to track signals in environments where other receivers fail. Obtain lock sooner, and track longer with Fence Antenna technology.



GNSS Tracking	
Number of Channels	226 Channels with Universal Tracking Technology
GPS	L1, L2, L2C
GLONASS	L1, L2
SBAS	L1 C/A WAAS/MSAS/EGNOS/GAGAN
QZSS	L1 C/A
Positioning Accuracy	
Static/Fast Static	H: 3.0 mm + 0.4 ppm V: 5.0 mm + 0.5 ppm
Precision Static**	H: 3.0 mm + 0.1 ppm V: 3.5 mm + 0.4 ppm
RTK (L1 + L2)	H: 5 mm + 0.5 ppm V: 10 mm + 0.8 ppm
DGPS	< 0.5 m
Communication	
Bluetooth®	V 2.1 + EDR, Class 2, 115,200 bps
Radio	UHF, Spread Spectrum, Cellular (options)
Cellular	Integrated HSPA+/CDMA
Data and Memory	
Real Time Data Output	TPS, RTCM SC104 v2.x, 3.x and MSM, CMR/CMR+
NMEA 0183 Output	Version 2.x, 3.x and 4.x
Physical	
Dimensions (d x h)	184 x 95 mm
Weight	1 kg
Power	
Power Source	External Power (6.7 to 8 VDC) Removeable battery (7.2V, 4300 mAh)
Operating Time	> 7.5 hours
Environmental	
Operating Temp.	-40°C to 65°C
Dust/Water Rating	IP67
Drop and Topple	2 meter pole-drop

** Under nominal observing conditions and strict processing methods, including use of dual frequency GPS, precise ephemerides, calm ionospheric conditions, approved antenna calibration, unobstructed visibility above 10 degrees and an observation duration of at least 3 hours (dependent on baseline length).



Integrated radio and modem options

- Spread Spectrum radio
- Digital UHF II radio
- HSPA cellular modem
- CDMA modem

Project site ruggedness

- Magnesium metal housing
- 2 meter drop design
- Field tested, field ready
- Waterproof

Constellation tracking performance

- Full GPS, GLONASS, and SBAS constellation and signal tracking
- Delivering positional confidence in harsh environments
- Improved repeatability 24/7

Housing features

- Multifunction communication
- Sealed power port for full day use
- Sealed external serial port
- Certified slant height measure mark



For more information:
topconpositioning.com/hiper-v

Specifications subject to change without notice.
©2017 Topcon Corporation All rights reserved.
7010-2121 E 4/17

The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Topcon is under license. Other trademarks and trade names are those of their respective owners.

